

HB 性能

13.6m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 7.0 | 84.0 | | | | |
| 8.0 | 84.0 | 84.0 | | | |
| 9.0 | 84.0 | 80.1 | | | |
| 10.0 | 76.8 | 76.0 | 65.8 | | |
| 11.0 | 68.8 | 70.5 | 63.2 | | |
| 12.0 | 62.0 | 63.6 | 60.7 | 50.9 | |
| 14.0 | 51.5 | 52.7 | 53.9 | 48.1 | 34.2 |
| 16.0 | 42.5 | 43.4 | 44.3 | 45.4 | 33.3 |
| 18.0 | 35.3 | 36.0 | 36.7 | 37.5 | 32.7 |
| 20.0 | 29.9 | 30.4 | 30.9 | 31.5 | |
| 22.0 | 25.7 | 26.1 | 26.5 | 26.8 | |
| 24.0 | 22.3 | 22.6 | 22.9 | | |
| 26.0 | 19.6 | 19.8 | 19.9 | | |
| 28.0 | 17.3 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 120t | 120t | 120t | 120t | 120t |
| フック質量 (t) | 1.90 | 1.90 | 1.90 | 1.90 | 1.90 |
| 巻掛本数 | 8 | 8 | 8 | 8 | 8 |

HB 性能

22.7m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 8.0 | 64.0 | | | | |
| 9.0 | 64.0 | | | | |
| 10.0 | 64.0 | 64.0 | | | |
| 11.0 | 64.0 | 64.0 | | | |
| 12.0 | 58.4 | 60.7 | 62.8 | | |
| 14.0 | 47.8 | 49.7 | 51.4 | 51.8 | |
| 16.0 | 39.2 | 40.6 | 41.9 | 43.6 | 38.6 |
| 18.0 | 32.1 | 33.2 | 34.3 | 35.6 | 36.5 |
| 20.0 | 26.7 | 27.7 | 28.6 | 29.6 | 30.3 |
| 22.0 | 22.6 | 23.4 | 24.1 | 24.9 | 25.4 |
| 24.0 | 19.2 | 19.9 | 20.5 | 21.1 | |
| 26.0 | 16.5 | 17.1 | 17.6 | 18.0 | |
| 28.0 | 14.3 | 14.7 | 15.1 | 15.4 | |
| 30.0 | 12.4 | 12.7 | 13.0 | | |
| 32.0 | 10.7 | 11.0 | 11.2 | | |
| 34.0 | 9.3 | 9.5 | 9.6 | | |
| 36.0 | 8.1 | 8.2 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 6 | 6 | 6 | 6 | 6 |

HB 性能

18.15m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 7.0 | 77.0 | | | | |
| 8.0 | 77.0 | | | | |
| 9.0 | 77.0 | 77.0 | | | |
| 10.0 | 74.7 | 77.0 | | | |
| 11.0 | 66.6 | 68.8 | 65.2 | | |
| 12.0 | 59.9 | 61.8 | 63.0 | | |
| 14.0 | 49.3 | 50.9 | 52.4 | 50.6 | |
| 16.0 | 40.6 | 41.7 | 42.9 | 44.3 | 36.2 |
| 18.0 | 33.4 | 34.3 | 35.2 | 36.3 | 35.5 |
| 20.0 | 28.0 | 28.8 | 29.5 | 30.3 | 30.8 |
| 22.0 | 23.8 | 24.5 | 25.0 | 25.7 | |
| 24.0 | 20.5 | 21.0 | 21.5 | 21.9 | |
| 26.0 | 17.8 | 18.2 | 18.5 | 18.8 | |
| 28.0 | 15.5 | 15.8 | 16.0 | | |
| 30.0 | 13.6 | 13.8 | 13.9 | | |
| 32.0 | 12.0 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 120t | 120t | 120t | 120t | 120t |
| フック質量 (t) | 1.90 | 1.90 | 1.90 | 1.90 | 1.90 |
| 巻掛本数 | 8 | 8 | 8 | 8 | 8 |

HB 性能

31.8m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 10.0 | 45.0 | | | | |
| 11.0 | 44.8 | 40.3 | | | |
| 12.0 | 44.1 | 39.8 | | | |
| 14.0 | 42.8 | 38.8 | 35.3 | | |
| 16.0 | 39.1 | 38.0 | 34.7 | 30.2 | |
| 18.0 | 31.9 | 33.2 | 34.1 | 29.8 | 25.8 |
| 20.0 | 26.6 | 27.6 | 28.6 | 29.6 | 25.8 |
| 22.0 | 22.4 | 23.3 | 24.1 | 25.1 | 25.7 |
| 24.0 | 19.1 | 19.9 | 20.6 | 21.4 | 21.8 |
| 26.0 | 16.4 | 17.0 | 17.6 | 18.3 | 18.6 |
| 28.0 | 14.1 | 14.7 | 15.2 | 15.7 | 16.0 |
| 30.0 | 12.2 | 12.7 | 13.1 | 13.6 | |
| 32.0 | 10.5 | 11.0 | 11.3 | 11.7 | |
| 34.0 | 9.1 | 9.5 | 9.8 | 10.0 | |
| 36.0 | 7.9 | 8.2 | 8.4 | | |
| 38.0 | 6.8 | 7.0 | 7.2 | | |
| 40.0 | 5.7 | 6.0 | 6.1 | | |
| 42.0 | 4.5 | 4.7 | | | |
| 44.0 | 3.5 | 3.6 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HB 性能

13.6m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 10.0 | 54.0 | | | | |
| 11.0 | 54.0 | | | | |
| 12.0 | 54.0 | | | | |
| 14.0 | 53.9 | 47.4 | | | |
| 16.0 | 44.8 | 43.1 | 38.0 | | |
| 18.0 | 37.4 | 38.6 | 35.3 | | |
| 20.0 | 31.8 | 32.8 | 33.0 | 28.1 | |
| 22.0 | 27.5 | 28.4 | 29.2 | 26.8 | 19.4 |
| 24.0 | 24.0 | 24.8 | 25.5 | 25.7 | 18.9 |
| 26.0 | 21.2 | 21.8 | 22.4 | 23.3 | 18.6 |
| 28.0 | 18.9 | 19.4 | 19.9 | 20.5 | 18.4 |
| 30.0 | 16.9 | 17.3 | 17.7 | 18.2 | |
| 32.0 | 15.2 | 15.5 | 15.8 | 16.1 | |
| 34.0 | 13.7 | 14.0 | 14.2 | | |
| 36.0 | 12.5 | 12.6 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 6 | 6 | 6 | 6 | 6 |

HB 性能

22.7m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 11.0 | 45.0 | | | | |
| 12.0 | 45.0 | | | | |
| 14.0 | 45.0 | | | | |
| 16.0 | 42.2 | 44.4 | | | |
| 18.0 | 34.8 | 36.6 | 38.4 | | |
| 20.0 | 29.2 | 30.8 | 32.3 | | |
| 22.0 | 24.9 | 26.3 | 27.6 | 29.4 | |
| 24.0 | 21.5 | 22.7 | 23.8 | 25.3 | 22.1 |
| 26.0 | 18.7 | 19.7 | 20.7 | 22.0 | 21.7 |
| 28.0 | 16.3 | 17.2 | 18.1 | 19.2 | 19.9 |
| 30.0 | 14.3 | 15.1 | 15.9 | 16.8 | 17.4 |
| 32.0 | 12.6 | 13.3 | 13.9 | 14.7 | 15.1 |
| 34.0 | 11.1 | 11.7 | 12.3 | 12.9 | |
| 36.0 | 9.9 | 10.4 | 10.8 | 11.3 | |
| 38.0 | 8.7 | 9.2 | 9.5 | 9.8 | |
| 40.0 | 7.7 | 8.1 | 8.3 | | |
| 42.0 | 6.8 | 7.1 | 7.2 | | |
| 44.0 | 6.0 | 6.2 | | | |
| 46.0 | 5.2 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HB 性能

18.15m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 10.0 | 50.0 | | | | |
| 11.0 | 50.0 | | | | |
| 12.0 | 50.0 | | | | |
| 14.0 | 50.0 | 49.4 | | | |
| 16.0 | 43.2 | 45.0 | | | |
| 18.0 | 35.8 | 37.4 | 36.4 | | |
| 20.0 | 30.3 | 31.6 | 32.9 | | |
| 22.0 | 26.0 | 27.1 | 28.2 | 28.2 | |
| 24.0 | 22.5 | 23.5 | 24.4 | 25.7 | 20.6 |
| 26.0 | 19.7 | 20.5 | 21.3 | 22.4 | 20.2 |
| 28.0 | 17.4 | 18.1 | 18.8 | 19.7 | 19.9 |
| 30.0 | 15.4 | 16.0 | 16.6 | 17.3 | 17.7 |
| 32.0 | 13.7 | 14.2 | 14.7 | 15.3 | |
| 34.0 | 12.2 | 12.7 | 13.1 | 13.5 | |
| 36.0 | 10.9 | 11.3 | 11.6 | | |
| 38.0 | 9.8 | 10.1 | 10.3 | | |
| 40.0 | 8.8 | 9.0 | | | |
| 42.0 | 7.9 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 6 | 6 | 6 | 6 | 6 |

HB 性能

31.8m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 14.0 | 30.0 | | | | |
| 16.0 | 30.0 | 29.8 | | | |
| 18.0 | 30.0 | 28.9 | | | |
| 20.0 | 28.6 | 28.0 | 25.2 | | |
| 22.0 | 24.3 | 25.8 | 24.6 | | |
| 24.0 | 20.8 | 22.2 | 23.4 | 20.6 | |
| 26.0 | 18.0 | 19.2 | 20.3 | 20.3 | 17.0 |
| 28.0 | 15.7 | 16.7 | 17.7 | 19.0 | 16.9 |
| 30.0 | 13.7 | 14.7 | 15.5 | 16.6 | 16.9 |
| 32.0 | 12.0 | 12.9 | 13.6 | 14.6 | 15.2 |
| 34.0 | 10.6 | 11.3 | 12.0 | 12.8 | 13.3 |
| 36.0 | 9.3 | 9.9 | 10.5 | 11.3 | 11.6 |
| 38.0 | 8.1 | 8.7 | 9.3 | 9.9 | |
| 40.0 | 7.1 | 7.7 | 8.1 | 8.6 | |
| 42.0 | 6.2 | 6.7 | 7.1 | 7.5 | |
| 44.0 | 5.4 | 5.8 | 6.2 | 6.4 | |
| 46.0 | 4.4 | 4.9 | 5.3 | | |
| 48.0 | 3.5 | 4.0 | 4.3 | | |
| 50.0 | | 3.1 | 3.2 | | |
| 危険角度 (°) | 24 | 24 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HB 性能

40.9m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 20.0 | | | | |
| 18.0 | 20.0 | | | | |
| 20.0 | 20.0 | 20.0 | | | |
| 22.0 | 20.0 | 20.0 | 20.0 | | |
| 24.0 | 20.0 | 20.0 | 20.0 | | |
| 26.0 | 17.9 | 19.2 | 20.0 | 20.0 | |
| 28.0 | 15.5 | 16.7 | 17.7 | 19.1 | 20.0 |
| 30.0 | 13.6 | 14.6 | 15.5 | 16.7 | 17.6 |
| 32.0 | 11.9 | 12.8 | 13.6 | 14.7 | 15.4 |
| 34.0 | 10.4 | 11.2 | 12.0 | 12.9 | 13.5 |
| 36.0 | 9.1 | 9.9 | 10.5 | 11.4 | 11.9 |
| 38.0 | 8.0 | 8.6 | 9.3 | 10.0 | 10.4 |
| 40.0 | 6.9 | 7.6 | 8.1 | 8.8 | 9.1 |
| 42.0 | 6.0 | 6.6 | 7.1 | 7.7 | |
| 44.0 | 5.0 | 5.7 | 6.2 | 6.6 | |
| 46.0 | 4.1 | 4.8 | 5.3 | 5.7 | |
| 48.0 | 3.2 | 3.8 | 4.3 | 4.7 | |
| 50.0 | | 2.9 | 3.3 | 3.7 | |
| 危険角度 (°) | 40 | 41 | 41 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

50.0m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 11.0 | | | | |
| 20.0 | 11.0 | | | | |
| 22.0 | 11.0 | 11.0 | | | |
| 24.0 | 11.0 | 11.0 | 11.0 | | |
| 26.0 | 11.0 | 11.0 | 11.0 | | |
| 28.0 | 11.0 | 11.0 | 10.9 | 9.1 | |
| 30.0 | 11.0 | 11.0 | 10.8 | 9.1 | 7.5 |
| 32.0 | 11.0 | 11.0 | 10.6 | 9.0 | 7.5 |
| 34.0 | 10.0 | 10.9 | 10.5 | 9.0 | 7.5 |
| 36.0 | 8.7 | 9.6 | 10.3 | 8.9 | 7.5 |
| 38.0 | 7.6 | 8.4 | 9.1 | 8.9 | 7.5 |
| 40.0 | 6.6 | 7.3 | 7.9 | 8.7 | 7.5 |
| 42.0 | 5.6 | 6.3 | 6.9 | 7.6 | 7.5 |
| 44.0 | 4.5 | 5.4 | 6.0 | 6.6 | 6.9 |
| 46.0 | 3.6 | 4.4 | 5.1 | 5.7 | |
| 48.0 | 2.7 | 3.4 | 4.1 | 4.7 | |
| 50.0 | | | 3.1 | 3.7 | |
| 危険角度 (°) | 50 | 50 | 51 | 51 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

45.5m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 16.0 | | | | |
| 18.0 | 16.0 | | | | |
| 20.0 | 16.0 | 16.0 | | | |
| 22.0 | 16.0 | 16.0 | | | |
| 24.0 | 16.0 | 16.0 | 16.0 | | |
| 26.0 | 16.0 | 16.0 | 16.0 | | |
| 28.0 | 15.4 | 16.0 | 16.0 | 15.6 | |
| 30.0 | 13.4 | 14.4 | 15.4 | 15.4 | 13.0 |
| 32.0 | 11.7 | 12.6 | 13.5 | 14.6 | 13.0 |
| 34.0 | 10.2 | 11.1 | 11.9 | 12.9 | 12.9 |
| 36.0 | 8.9 | 9.7 | 10.4 | 11.3 | 11.9 |
| 38.0 | 7.8 | 8.5 | 9.2 | 9.9 | 10.4 |
| 40.0 | 6.8 | 7.4 | 8.0 | 8.7 | 9.1 |
| 42.0 | 5.9 | 6.5 | 7.0 | 7.6 | 7.9 |
| 44.0 | 4.8 | 5.6 | 6.1 | 6.6 | |
| 46.0 | 3.8 | 4.6 | 5.2 | 5.7 | |
| 48.0 | 2.9 | 3.6 | 4.2 | 4.8 | |
| 50.0 | | 2.7 | 3.2 | 3.7 | |
| 危険角度 (°) | 46 | 46 | 47 | 47 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

13.6m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 14.0 | 35.0 | | | | |
| 16.0 | 34.4 | | | | |
| 18.0 | 34.4 | 33.8 | | | |
| 20.0 | 33.2 | 31.5 | | | |
| 22.0 | 28.7 | 29.1 | 26.1 | | |
| 24.0 | 25.2 | 26.2 | 24.5 | | |
| 26.0 | 22.3 | 23.2 | 23.1 | | |
| 28.0 | 19.9 | 20.7 | 21.5 | 18.8 | |
| 30.0 | 17.9 | 18.6 | 19.3 | 18.0 | |
| 32.0 | 16.2 | 16.8 | 17.4 | 17.3 | 12.7 |
| 34.0 | 14.7 | 15.2 | 15.7 | 16.5 | 12.4 |
| 36.0 | 13.3 | 13.8 | 14.3 | 14.9 | 12.2 |
| 38.0 | 12.2 | 12.6 | 13.0 | 13.5 | |
| 40.0 | 11.2 | 11.5 | 11.8 | 12.2 | |
| 42.0 | 10.2 | 10.5 | 10.7 | | |
| 44.0 | 9.4 | 9.6 | 9.7 | | |
| 46.0 | 8.7 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HB 性能

22.7m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 30.0 | | | | |
| 18.0 | 30.0 | | | | |
| 20.0 | 30.0 | 30.0 | | | |
| 22.0 | 26.4 | 28.2 | | | |
| 24.0 | 22.8 | 24.4 | 25.8 | | |
| 26.0 | 20.0 | 21.4 | 22.8 | | |
| 28.0 | 17.6 | 18.8 | 20.1 | | |
| 30.0 | 15.5 | 16.7 | 17.8 | 19.3 | |
| 32.0 | 13.8 | 14.8 | 15.8 | 17.2 | |
| 34.0 | 12.3 | 13.2 | 14.1 | 15.3 | 14.5 |
| 36.0 | 11.0 | 11.8 | 12.6 | 13.7 | 14.2 |
| 38.0 | 9.8 | 10.5 | 11.3 | 12.2 | 12.9 |
| 40.0 | 8.8 | 9.4 | 10.1 | 10.9 | 11.4 |
| 42.0 | 7.8 | 8.4 | 9.0 | 9.7 | |
| 44.0 | 7.0 | 7.5 | 8.0 | 8.6 | |
| 46.0 | 6.3 | 6.7 | 7.1 | 7.6 | |
| 48.0 | 5.6 | 6.0 | 6.3 | | |
| 50.0 | 5.0 | 5.3 | 5.5 | | |
| 55.0 | 3.2 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HB 性能

18.15m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 14.0 | 34.0 | | | | |
| 16.0 | 34.0 | | | | |
| 18.0 | 34.0 | 34.0 | | | |
| 20.0 | 31.9 | 32.8 | | | |
| 22.0 | 27.5 | 29.0 | 26.8 | | |
| 24.0 | 23.9 | 25.3 | 25.2 | | |
| 26.0 | 21.1 | 22.2 | 23.4 | | |
| 28.0 | 18.7 | 19.7 | 20.7 | 19.8 | |
| 30.0 | 16.6 | 17.6 | 18.5 | 19.1 | |
| 32.0 | 14.9 | 15.7 | 16.5 | 17.7 | 13.9 |
| 34.0 | 13.4 | 14.1 | 14.8 | 15.9 | 13.6 |
| 36.0 | 12.1 | 12.7 | 13.4 | 14.2 | 13.4 |
| 38.0 | 10.9 | 11.5 | 12.0 | 12.8 | 13.2 |
| 40.0 | 9.9 | 10.4 | 10.9 | 11.5 | |
| 42.0 | 8.9 | 9.4 | 9.8 | 10.3 | |
| 44.0 | 8.1 | 8.5 | 8.8 | 9.2 | |
| 46.0 | 7.4 | 7.7 | 7.9 | | |
| 48.0 | 6.7 | 6.9 | 7.0 | | |
| 50.0 | 6.1 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HB 性能

31.8m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 20.0 | | | | |
| 18.0 | 20.0 | | | | |
| 20.0 | 20.0 | | | | |
| 22.0 | 20.0 | 20.0 | | | |
| 24.0 | 20.0 | 20.0 | | | |
| 26.0 | 19.6 | 20.0 | 19.4 | | |
| 28.0 | 17.2 | 18.6 | 18.9 | | |
| 30.0 | 15.1 | 16.4 | 17.7 | 15.6 | |
| 32.0 | 13.4 | 14.6 | 15.7 | 15.3 | |
| 34.0 | 11.9 | 12.9 | 13.9 | 15.1 | 12.4 |
| 36.0 | 10.5 | 11.5 | 12.4 | 13.7 | 12.3 |
| 38.0 | 9.4 | 10.3 | 11.1 | 12.2 | 12.3 |
| 40.0 | 8.3 | 9.1 | 9.9 | 10.9 | 11.6 |
| 42.0 | 7.4 | 8.1 | 8.8 | 9.7 | 10.3 |
| 44.0 | 6.6 | 7.2 | 7.9 | 8.6 | 9.1 |
| 46.0 | 5.8 | 6.4 | 7.0 | 7.6 | 8.0 |
| 48.0 | 5.1 | 5.7 | 6.2 | 6.7 | |
| 50.0 | 4.3 | 5.0 | 5.4 | 5.9 | |
| 55.0 | | 3.0 | 3.4 | | |
| 危険角度 (°) | 33 | 33 | 34 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

40.9m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 14.0 | | | | |
| 20.0 | 14.0 | | | | |
| 22.0 | 14.0 | | | | |
| 24.0 | 14.0 | 14.0 | | | |
| 26.0 | 14.0 | 14.0 | | | |
| 28.0 | 14.0 | 14.0 | 14.0 | | |
| 30.0 | 14.0 | 14.0 | 14.0 | | |
| 32.0 | 12.9 | 14.0 | 14.0 | | |
| 34.0 | 11.4 | 12.5 | 13.6 | 14.0 | |
| 36.0 | 10.0 | 11.1 | 12.1 | 13.5 | |
| 38.0 | 8.9 | 9.9 | 10.8 | 12.0 | 13.0 |
| 40.0 | 7.8 | 8.7 | 9.6 | 10.7 | 11.5 |
| 42.0 | 6.9 | 7.7 | 8.5 | 9.5 | 10.2 |
| 44.0 | 6.1 | 6.8 | 7.6 | 8.5 | 9.1 |
| 46.0 | 5.3 | 6.0 | 6.7 | 7.5 | 8.0 |
| 48.0 | 4.4 | 5.3 | 5.9 | 6.6 | 7.0 |
| 50.0 | 3.5 | 4.4 | 5.1 | 5.8 | 6.1 |
| 55.0 | | | | 3.7 | |
| 危険角度 (°) | 46 | 47 | 47 | 48 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

50.0m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.0 | | | | |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | 9.0 | | | |
| 28.0 | 9.0 | 9.0 | | | |
| 30.0 | 9.0 | 9.0 | 7.8 | | |
| 32.0 | 9.0 | 8.8 | 7.7 | | |
| 34.0 | 9.0 | 8.6 | 7.5 | | |
| 36.0 | 9.0 | 8.4 | 7.4 | 6.0 | |
| 38.0 | 8.4 | 8.2 | 7.3 | 5.9 | 4.7 |
| 40.0 | 7.4 | 8.1 | 7.2 | 5.9 | 4.6 |
| 42.0 | 6.5 | 7.4 | 7.1 | 5.8 | 4.6 |
| 44.0 | 5.6 | 6.5 | 7.0 | 5.8 | 4.6 |
| 46.0 | 4.7 | 5.7 | 6.4 | 5.8 | 4.6 |
| 48.0 | 3.7 | 4.8 | 5.6 | 5.8 | 4.6 |
| 50.0 | | 3.9 | 4.9 | 5.7 | 4.6 |
| 55.0 | | | | 3.6 | |
| 危険角度 (°) | 55 | 56 | 56 | 56 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

45.5m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 11.1 | 12.0 | 12.0 | 11.1 | |
| 36.0 | 9.8 | 10.9 | 12.0 | 11.0 | |
| 38.0 | 8.6 | 9.7 | 10.6 | 10.9 | 8.9 |
| 40.0 | 7.6 | 8.6 | 9.5 | 10.6 | 8.9 |
| 42.0 | 6.7 | 7.6 | 8.4 | 9.5 | 8.8 |
| 44.0 | 5.8 | 6.7 | 7.4 | 8.4 | 8.8 |
| 46.0 | 4.9 | 5.8 | 6.5 | 7.4 | 8.0 |
| 48.0 | 4.0 | 5.1 | 5.7 | 6.5 | 7.0 |
| 50.0 | 3.2 | 4.2 | 5.0 | 5.7 | 6.1 |
| 55.0 | | | 2.9 | 3.7 | |
| 危険角度 (°) | 50 | 51 | 51 | 52 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HB 性能

13.6m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 12.0 | | | | |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | 12.0 | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | 12.0 | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | 11.8 | |
| 38.0 | 12.0 | 12.0 | 12.0 | 11.2 | |
| 40.0 | 12.0 | 12.0 | 11.9 | 10.7 | 9.4 |
| 42.0 | 11.2 | 11.7 | 11.3 | 10.2 | 9.2 |
| 44.0 | 10.3 | 10.7 | 10.7 | 9.8 | 9.0 |
| 46.0 | 9.6 | 9.9 | 10.3 | 9.5 | 8.9 |
| 48.0 | 8.8 | 9.2 | 9.5 | 9.2 | |
| 50.0 | 8.2 | 8.5 | 8.7 | 9.0 | |
| 55.0 | 6.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

22.7m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | 12.0 | |
| 38.0 | 11.2 | 12.0 | 12.0 | 11.7 | |
| 40.0 | 10.1 | 11.0 | 11.9 | 11.3 | |
| 42.0 | 9.1 | 10.0 | 10.8 | 10.8 | 9.7 |
| 44.0 | 8.3 | 9.0 | 9.8 | 10.5 | 9.5 |
| 46.0 | 7.5 | 8.2 | 8.9 | 9.8 | 9.3 |
| 48.0 | 6.8 | 7.4 | 8.0 | 8.8 | 9.1 |
| 50.0 | 6.1 | 6.7 | 7.3 | 8.0 | 8.4 |
| 55.0 | 4.7 | 5.2 | 5.5 | 6.0 | |
| 60.0 | 3.3 | 3.7 | 3.9 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

18.15m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | 12.0 | |
| 38.0 | 12.0 | 12.0 | 12.0 | 11.5 | |
| 40.0 | 11.0 | 11.8 | 12.0 | 11.0 | 9.9 |
| 42.0 | 10.1 | 10.8 | 11.4 | 10.6 | 9.6 |
| 44.0 | 9.2 | 9.8 | 10.4 | 10.2 | 9.3 |
| 46.0 | 8.5 | 9.0 | 9.5 | 9.8 | 9.2 |
| 48.0 | 7.8 | 8.2 | 8.7 | 9.3 | 9.0 |
| 50.0 | 7.1 | 7.5 | 7.9 | 8.5 | |
| 55.0 | 5.7 | 6.0 | 6.2 | | |
| 60.0 | 4.5 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

31.8m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 11.7 | 12.0 | 12.0 | | |
| 38.0 | 10.5 | 11.6 | 12.0 | 12.0 | |
| 40.0 | 9.5 | 10.5 | 11.5 | 11.7 | |
| 42.0 | 8.5 | 9.5 | 10.4 | 11.3 | |
| 44.0 | 7.6 | 8.5 | 9.4 | 10.6 | 9.5 |
| 46.0 | 6.9 | 7.7 | 8.5 | 9.6 | 9.4 |
| 48.0 | 6.2 | 6.9 | 7.7 | 8.6 | 9.3 |
| 50.0 | 5.5 | 6.2 | 6.9 | 7.8 | 8.4 |
| 55.0 | 3.9 | 4.7 | 5.2 | 5.9 | 6.2 |
| 60.0 | 2.4 | 3.0 | 3.6 | 4.2 | |
| 65.0 | | 1.5 | 1.9 | | |
| 危険角度 (°) | 32 | 33 | 33 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

40.9m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 11.0 | | | | |
| 24.0 | 11.0 | | | | |
| 26.0 | 11.0 | | | | |
| 28.0 | 11.0 | 11.0 | | | |
| 30.0 | 11.0 | 11.0 | | | |
| 32.0 | 11.0 | 11.0 | | | |
| 34.0 | 11.0 | 11.0 | 11.0 | | |
| 36.0 | 11.0 | 11.0 | 11.0 | | |
| 38.0 | 10.0 | 11.0 | 11.0 | | |
| 40.0 | 8.9 | 10.1 | 11.0 | | |
| 42.0 | 8.0 | 9.1 | 10.1 | 11.0 | |
| 44.0 | 7.1 | 8.1 | 9.1 | 10.4 | |
| 46.0 | 6.3 | 7.3 | 8.2 | 9.4 | 9.6 |
| 48.0 | 5.6 | 6.5 | 7.3 | 8.5 | 9.3 |
| 50.0 | 5.0 | 5.8 | 6.6 | 7.6 | 8.4 |
| 55.0 | 3.1 | 4.1 | 4.9 | 5.7 | 6.3 |
| 60.0 | 1.6 | 2.4 | 3.2 | 4.1 | |
| 65.0 | | | 1.6 | 2.2 | |
| 危険角度 (°) | 45 | 46 | 47 | 47 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

50.0m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 7.0 | | | | |
| 26.0 | 7.0 | | | | |
| 28.0 | 7.0 | | | | |
| 30.0 | 7.0 | 7.0 | | | |
| 32.0 | 7.0 | 7.0 | | | |
| 34.0 | 7.0 | 7.0 | | | |
| 36.0 | 7.0 | 6.8 | 5.9 | | |
| 38.0 | 7.0 | 6.7 | 5.8 | | |
| 40.0 | 7.0 | 6.5 | 5.6 | | |
| 42.0 | 7.0 | 6.4 | 5.5 | | |
| 44.0 | 6.7 | 6.2 | 5.4 | 4.3 | |
| 46.0 | 5.9 | 6.1 | 5.3 | 4.2 | |
| 48.0 | 5.2 | 6.0 | 5.2 | 4.2 | 3.1 |
| 50.0 | 4.3 | 5.4 | 5.2 | 4.1 | 3.1 |
| 55.0 | | 3.6 | 4.6 | 4.1 | 3.1 |
| 60.0 | | | 2.8 | 3.9 | 3.1 |
| 65.0 | | | | 2.1 | |
| 危険角度 (°) | 56 | 57 | 57 | 57 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

45.5m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 10.0 | | | | |
| 26.0 | 10.0 | | | | |
| 28.0 | 10.0 | | | | |
| 30.0 | 10.0 | 10.0 | | | |
| 32.0 | 10.0 | 10.0 | | | |
| 34.0 | 10.0 | 10.0 | | | |
| 36.0 | 10.0 | 10.0 | 10.0 | | |
| 38.0 | 9.8 | 10.0 | 10.0 | | |
| 40.0 | 8.7 | 9.9 | 10.0 | | |
| 42.0 | 7.7 | 8.9 | 10.0 | 8.5 | |
| 44.0 | 6.9 | 7.9 | 8.9 | 8.3 | |
| 46.0 | 6.1 | 7.1 | 8.0 | 8.2 | 6.6 |
| 48.0 | 5.4 | 6.3 | 7.2 | 8.1 | 6.5 |
| 50.0 | 4.6 | 5.6 | 6.4 | 7.5 | 6.5 |
| 55.0 | 2.8 | 3.9 | 4.8 | 5.7 | 6.2 |
| 60.0 | | 2.2 | 3.0 | 4.0 | 4.5 |
| 65.0 | | | | 2.2 | |
| 危険角度 (°) | 51 | 52 | 52 | 53 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

13.6m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 11.7 | | |
| 38.0 | 12.0 | 12.0 | 10.9 | | |
| 40.0 | 12.0 | 11.2 | 10.3 | | |
| 42.0 | 11.5 | 10.5 | 9.7 | 8.6 | |
| 44.0 | 10.6 | 9.9 | 9.2 | 8.2 | |
| 46.0 | 9.8 | 9.4 | 8.7 | 7.8 | 7.1 |
| 48.0 | 9.1 | 8.8 | 8.2 | 7.5 | 6.9 |
| 50.0 | 8.5 | 8.4 | 7.9 | 7.2 | 6.7 |
| 55.0 | 7.1 | 7.4 | 7.1 | 6.6 | |
| 60.0 | 5.9 | 6.1 | 6.2 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

22.7m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 11.7 | 12.0 | 11.7 | | |
| 40.0 | 10.6 | 11.6 | 11.1 | | |
| 42.0 | 9.6 | 10.6 | 10.5 | 8.9 | |
| 44.0 | 8.8 | 9.6 | 10.0 | 8.6 | |
| 46.0 | 8.0 | 8.8 | 9.5 | 8.2 | |
| 48.0 | 7.2 | 8.0 | 8.8 | 7.9 | 7.1 |
| 50.0 | 6.6 | 7.3 | 8.0 | 7.6 | 6.9 |
| 55.0 | 5.2 | 5.8 | 6.3 | 7.0 | 6.5 |
| 60.0 | 3.9 | 4.5 | 4.9 | 5.4 | |
| 65.0 | 2.6 | 3.1 | 3.5 | | |
| 70.0 | 1.4 | 1.6 | | | |
| 危険角度 (°) | 14 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

18.15m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 12.0 | 12.0 | 11.3 | | |
| 40.0 | 11.5 | 12.0 | 10.7 | | |
| 42.0 | 10.5 | 11.2 | 10.1 | 8.8 | |
| 44.0 | 9.6 | 10.3 | 9.6 | 8.4 | |
| 46.0 | 8.8 | 9.5 | 9.1 | 8.0 | |
| 48.0 | 8.1 | 8.7 | 8.7 | 7.7 | 7.0 |
| 50.0 | 7.5 | 8.0 | 8.3 | 7.4 | 6.8 |
| 55.0 | 6.1 | 6.5 | 6.9 | 6.8 | 6.5 |
| 60.0 | 4.9 | 5.2 | 5.5 | 5.8 | |
| 65.0 | 3.9 | 4.1 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

31.8m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | | | | |
| 28.0 | 12.0 | | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | | | |
| 34.0 | 12.0 | 12.0 | | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 11.0 | 12.0 | 12.0 | | |
| 40.0 | 9.9 | 11.1 | 11.8 | | |
| 42.0 | 9.0 | 10.1 | 11.2 | | |
| 44.0 | 8.1 | 9.1 | 10.2 | 8.8 | |
| 46.0 | 7.3 | 8.3 | 9.2 | 8.5 | |
| 48.0 | 6.6 | 7.5 | 8.4 | 8.2 | |
| 50.0 | 5.9 | 6.8 | 7.6 | 8.0 | 7.0 |
| 55.0 | 4.5 | 5.2 | 5.9 | 6.9 | 6.7 |
| 60.0 | 3.0 | 3.8 | 4.5 | 5.2 | 5.7 |
| 65.0 | 1.7 | 2.4 | 3.0 | 3.8 | |
| 70.0 | | | 1.6 | 2.0 | |
| 危険角度 (°) | 38 | 39 | 40 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

40.9m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 8.0 | | | | |
| 28.0 | 8.0 | | | | |
| 30.0 | 8.0 | | | | |
| 32.0 | 8.0 | 8.0 | | | |
| 34.0 | 8.0 | 8.0 | | | |
| 36.0 | 8.0 | 8.0 | | | |
| 38.0 | 8.0 | 8.0 | | | |
| 40.0 | 8.0 | 8.0 | 8.0 | | |
| 42.0 | 8.0 | 8.0 | 8.0 | | |
| 44.0 | 7.5 | 8.0 | 8.0 | | |
| 46.0 | 6.8 | 7.9 | 8.0 | | |
| 48.0 | 6.0 | 7.1 | 8.0 | 8.0 | |
| 50.0 | 5.4 | 6.4 | 7.3 | 8.0 | |
| 55.0 | 3.7 | 4.8 | 5.6 | 6.7 | 6.8 |
| 60.0 | 2.2 | 3.2 | 4.2 | 5.1 | 5.7 |
| 65.0 | | 1.7 | 2.6 | 3.6 | 4.1 |
| 70.0 | | | | 1.9 | |
| 危険角度 (°) | 49 | 50 | 51 | 51 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

50.0m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 5.0 | | | | |
| 28.0 | 5.0 | | | | |
| 30.0 | 5.0 | | | | |
| 32.0 | 5.0 | | | | |
| 34.0 | 5.0 | 5.0 | | | |
| 36.0 | 5.0 | 5.0 | | | |
| 38.0 | 5.0 | 5.0 | | | |
| 40.0 | 5.0 | 5.0 | 4.5 | | |
| 42.0 | 5.0 | 5.0 | 4.4 | | |
| 44.0 | 5.0 | 5.0 | 4.3 | | |
| 46.0 | 5.0 | 4.9 | 4.2 | | |
| 48.0 | 5.0 | 4.8 | 4.1 | 3.1 | |
| 50.0 | 4.9 | 4.7 | 4.0 | 3.0 | |
| 55.0 | | 4.4 | 3.8 | 2.9 | 2.0 |
| 60.0 | | 2.7 | 3.7 | 2.8 | 2.0 |
| 65.0 | | | | 2.8 | 2.0 |
| 70.0 | | | | | 2.0 |
| 危険角度 (°) | 59 | 59 | 60 | 60 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

45.5m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 7.5 | | | | |
| 28.0 | 7.5 | | | | |
| 30.0 | 7.5 | | | | |
| 32.0 | 7.5 | | | | |
| 34.0 | 7.5 | 7.5 | | | |
| 36.0 | 7.5 | 7.5 | | | |
| 38.0 | 7.5 | 7.5 | | | |
| 40.0 | 7.5 | 7.5 | 7.5 | | |
| 42.0 | 7.5 | 7.5 | 7.5 | | |
| 44.0 | 7.3 | 7.5 | 7.5 | | |
| 46.0 | 6.5 | 7.5 | 7.5 | | |
| 48.0 | 5.8 | 6.9 | 7.5 | 6.7 | |
| 50.0 | 5.1 | 6.2 | 7.1 | 6.6 | |
| 55.0 | 3.3 | 4.6 | 5.4 | 6.4 | 4.9 |
| 60.0 | | 2.9 | 4.0 | 5.0 | 4.9 |
| 65.0 | | | 2.4 | 3.5 | 4.1 |
| 70.0 | | | | 1.8 | |
| 危険角度 (°) | 54 | 55 | 56 | 56 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

13.6m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.3 | | | | |
| 26.0 | 9.3 | | | | |
| 28.0 | 9.3 | | | | |
| 30.0 | 9.1 | 8.9 | | | |
| 32.0 | 9.1 | 8.8 | | | |
| 34.0 | 9.0 | 8.8 | | | |
| 36.0 | 8.9 | 8.6 | | | |
| 38.0 | 8.7 | 8.2 | 7.7 | | |
| 40.0 | 8.4 | 7.9 | 7.4 | | |
| 42.0 | 8.0 | 7.6 | 7.2 | | |
| 44.0 | 7.7 | 7.3 | 6.9 | | |
| 46.0 | 7.4 | 7.0 | 6.7 | 6.2 | |
| 48.0 | 7.1 | 6.8 | 6.5 | 6.1 | |
| 50.0 | 6.9 | 6.6 | 6.3 | 5.9 | |
| 55.0 | 6.3 | 6.1 | 5.9 | 5.4 | 4.9 |
| 60.0 | 5.8 | 5.6 | 5.3 | 4.9 | 4.6 |
| 65.0 | 5.1 | 5.0 | 4.8 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

22.7m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 9.3 | | | | |
| 26.0 | 9.3 | | | | |
| 28.0 | 9.3 | | | | |
| 30.0 | 9.1 | | | | |
| 32.0 | 9.1 | 8.9 | | | |
| 34.0 | 9.1 | 8.8 | | | |
| 36.0 | 9.0 | 8.7 | | | |
| 38.0 | 8.9 | 8.6 | 7.9 | | |
| 40.0 | 8.8 | 8.3 | 7.7 | | |
| 42.0 | 8.7 | 8.0 | 7.4 | | |
| 44.0 | 8.4 | 7.7 | 7.2 | | |
| 46.0 | 8.1 | 7.5 | 7.0 | | |
| 48.0 | 7.6 | 7.2 | 6.8 | 6.2 | |
| 50.0 | 6.9 | 7.0 | 6.6 | 6.0 | |
| 55.0 | 5.5 | 6.2 | 6.2 | 5.7 | 5.1 |
| 60.0 | 4.3 | 4.9 | 5.5 | 5.2 | 4.8 |
| 65.0 | 3.1 | 3.8 | 4.3 | 4.8 | 4.6 |
| 70.0 | 2.0 | 2.5 | 3.0 | 3.5 | |
| 75.0 | | 1.3 | 1.5 | | |
| 危険角度 (°) | 24 | 24 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

18.15m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.3 | | | | |
| 26.0 | 9.3 | | | | |
| 28.0 | 9.3 | | | | |
| 30.0 | 9.1 | 9.0 | | | |
| 32.0 | 9.1 | 9.0 | | | |
| 34.0 | 9.1 | 8.9 | | | |
| 36.0 | 8.9 | 8.8 | | | |
| 38.0 | 8.8 | 8.4 | 7.8 | | |
| 40.0 | 8.7 | 8.1 | 7.6 | | |
| 42.0 | 8.4 | 7.8 | 7.3 | | |
| 44.0 | 8.0 | 7.5 | 7.1 | | |
| 46.0 | 7.7 | 7.3 | 6.8 | | |
| 48.0 | 7.5 | 7.0 | 6.6 | 6.1 | |
| 50.0 | 7.2 | 6.8 | 6.4 | 6.0 | |
| 55.0 | 6.3 | 6.3 | 6.0 | 5.5 | 5.0 |
| 60.0 | 5.2 | 5.6 | 5.6 | 5.0 | 4.7 |
| 65.0 | 4.2 | 4.5 | 4.9 | 4.7 | |
| 70.0 | 3.2 | 3.5 | 3.8 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

31.8m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | | | | |
| 32.0 | 9.0 | 8.9 | | | |
| 34.0 | 9.0 | 8.8 | | | |
| 36.0 | 9.0 | 8.7 | | | |
| 38.0 | 8.9 | 8.7 | | | |
| 40.0 | 8.8 | 8.7 | 7.9 | | |
| 42.0 | 8.7 | 8.4 | 7.6 | | |
| 44.0 | 8.5 | 8.1 | 7.4 | | |
| 46.0 | 7.7 | 7.9 | 7.2 | | |
| 48.0 | 6.9 | 7.6 | 7.0 | | |
| 50.0 | 6.3 | 7.2 | 6.8 | 6.1 | |
| 55.0 | 4.8 | 5.7 | 6.4 | 5.8 | |
| 60.0 | 3.4 | 4.4 | 5.1 | 5.5 | 4.9 |
| 65.0 | 2.1 | 3.0 | 3.9 | 4.7 | 4.7 |
| 70.0 | | 1.7 | 2.4 | 3.3 | |
| 75.0 | | | | 1.7 | |
| 危険角度 (°) | 45 | 45 | 45 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

40.9m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | | | | |
| 34.0 | 6.0 | | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | | | |
| 40.0 | 6.0 | 6.0 | | | |
| 42.0 | 6.0 | 6.0 | | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | | |
| 50.0 | 5.7 | 6.0 | 6.0 | | |
| 55.0 | 4.2 | 5.2 | 6.0 | 5.9 | |
| 60.0 | 2.6 | 3.8 | 4.7 | 5.7 | 4.9 |
| 65.0 | | 2.4 | 3.4 | 4.5 | 4.7 |
| 70.0 | | | 1.9 | 3.1 | 3.7 |
| 75.0 | | | | 1.6 | |
| 危険角度 (°) | 53 | 54 | 55 | 55 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

50.0m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | | | | |
| 34.0 | 4.1 | | | | |
| 36.0 | 4.1 | | | | |
| 38.0 | 4.1 | 4.1 | | | |
| 40.0 | 4.1 | 4.1 | | | |
| 42.0 | 4.1 | 4.1 | | | |
| 44.0 | 4.1 | 4.0 | | | |
| 46.0 | 4.1 | 3.9 | 3.2 | | |
| 48.0 | 4.1 | 3.8 | 3.1 | | |
| 50.0 | 4.1 | 3.7 | 3.0 | | |
| 55.0 | 3.5 | 3.4 | 2.8 | 2.0 | |
| 60.0 | | 3.2 | 2.7 | 1.9 | |
| 65.0 | | | 2.6 | 1.8 | |
| 70.0 | | | | 1.8 | |
| 危険角度 (°) | 61 | 62 | 63 | 64 | 64 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HB 性能

45.5m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | | | | |
| 34.0 | 5.5 | | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | | | |
| 42.0 | 5.5 | 5.5 | | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | | |
| 55.0 | 3.8 | 5.0 | 5.5 | 5.2 | |
| 60.0 | | 3.5 | 4.6 | 5.0 | 3.7 |
| 65.0 | | | 3.1 | 4.4 | 3.6 |
| 70.0 | | | | 2.9 | 3.6 |
| 75.0 | | | | | 2.0 |
| 危険角度 (°) | 58 | 59 | 59 | 60 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

13.6m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 7.0 | 84.0 | | | | |
| 8.0 | 84.0 | 84.0 | | | |
| 9.0 | 84.0 | 80.1 | | | |
| 10.0 | 80.8 | 76.0 | 65.8 | | |
| 11.0 | 75.6 | 72.2 | 63.2 | | |
| 12.0 | 70.0 | 68.9 | 60.7 | 50.9 | |
| 14.0 | 58.3 | 59.5 | 56.6 | 48.1 | 34.2 |
| 16.0 | 49.5 | 50.5 | 51.5 | 45.8 | 33.3 |
| 18.0 | 42.7 | 43.5 | 44.3 | 44.0 | 32.7 |
| 20.0 | 37.3 | 37.8 | 38.3 | 38.9 | |
| 22.0 | 32.3 | 32.7 | 33.0 | 33.4 | |
| 24.0 | 28.2 | 28.6 | 28.8 | | |
| 26.0 | 25.0 | 25.2 | 25.3 | | |
| 28.0 | 22.3 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 120t | 120t | 120t | 120t | 120t |
| フック質量 (t) | 1.90 | 1.90 | 1.90 | 1.90 | 1.90 |
| 巻掛本数 | 8 | 8 | 8 | 8 | 8 |

HA 性能

22.7m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 8.0 | 64.0 | | | | |
| 9.0 | 64.0 | | | | |
| 10.0 | 64.0 | 64.0 | | | |
| 11.0 | 64.0 | 64.0 | | | |
| 12.0 | 64.0 | 64.0 | 64.0 | | |
| 14.0 | 54.6 | 56.5 | 58.3 | 51.8 | |
| 16.0 | 45.8 | 47.4 | 48.9 | 49.8 | 38.6 |
| 18.0 | 39.0 | 40.3 | 41.5 | 43.1 | 37.8 |
| 20.0 | 33.5 | 34.6 | 35.7 | 36.9 | 37.3 |
| 22.0 | 29.0 | 30.0 | 30.7 | 31.5 | 31.9 |
| 24.0 | 25.2 | 25.8 | 26.4 | 27.1 | |
| 26.0 | 21.9 | 22.5 | 22.9 | 23.4 | |
| 28.0 | 19.2 | 19.7 | 20.0 | 20.4 | |
| 30.0 | 16.9 | 17.3 | 17.6 | | |
| 32.0 | 15.0 | 15.2 | 15.4 | | |
| 34.0 | 13.2 | 13.4 | 13.5 | | |
| 36.0 | 11.6 | 11.7 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 6 | 6 | 6 | 6 | 6 |

HA 性能

18.15m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 7.0 | 77.0 | | | | |
| 8.0 | 77.0 | | | | |
| 9.0 | 77.0 | 77.0 | | | |
| 10.0 | 77.0 | 77.0 | | | |
| 11.0 | 74.8 | 76.2 | 65.2 | | |
| 12.0 | 67.8 | 69.8 | 63.0 | | |
| 14.0 | 56.1 | 57.7 | 59.0 | 50.6 | |
| 16.0 | 47.3 | 48.6 | 49.9 | 48.4 | 36.2 |
| 18.0 | 40.5 | 41.6 | 42.6 | 43.9 | 35.5 |
| 20.0 | 35.0 | 36.0 | 36.8 | 37.7 | 35.1 |
| 22.0 | 30.4 | 31.1 | 31.6 | 32.2 | |
| 24.0 | 26.4 | 26.9 | 27.4 | 27.8 | |
| 26.0 | 23.2 | 23.6 | 23.9 | 24.2 | |
| 28.0 | 20.5 | 20.8 | 21.0 | | |
| 30.0 | 18.2 | 18.4 | 18.5 | | |
| 32.0 | 16.2 | 16.3 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 120t | 120t | 120t | 120t | 120t |
| フック質量 (t) | 1.90 | 1.90 | 1.90 | 1.90 | 1.90 |
| 巻掛本数 | 8 | 8 | 8 | 8 | 8 |

HA 性能

31.8m ブーム +4.4m+13.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 10.0 | 45.0 | | | | |
| 11.0 | 44.8 | 40.3 | | | |
| 12.0 | 44.1 | 39.8 | | | |
| 14.0 | 42.8 | 38.8 | 35.3 | | |
| 16.0 | 41.7 | 38.0 | 34.7 | 30.2 | |
| 18.0 | 38.8 | 37.2 | 34.1 | 29.8 | 25.8 |
| 20.0 | 33.3 | 34.6 | 33.7 | 29.6 | 25.8 |
| 22.0 | 28.8 | 29.9 | 30.7 | 29.5 | 25.8 |
| 24.0 | 25.0 | 25.8 | 26.5 | 27.3 | 25.8 |
| 26.0 | 21.7 | 22.4 | 23.0 | 23.7 | 24.0 |
| 28.0 | 19.0 | 19.6 | 20.1 | 20.7 | 20.9 |
| 30.0 | 16.7 | 17.2 | 17.7 | 18.1 | |
| 32.0 | 14.8 | 15.2 | 15.6 | 15.9 | |
| 34.0 | 13.0 | 13.4 | 13.7 | 14.0 | |
| 36.0 | 11.3 | 11.8 | 12.1 | | |
| 38.0 | 9.9 | 10.3 | 10.5 | | |
| 40.0 | 8.6 | 8.9 | 9.0 | | |
| 42.0 | 7.4 | 7.6 | | | |
| 44.0 | 6.4 | 6.5 | | | |
| 46.0 | 5.4 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HA 性能

13.6m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 10.0 | 54.0 | | | | |
| 11.0 | 54.0 | | | | |
| 12.0 | 54.0 | | | | |
| 14.0 | 54.0 | 47.4 | | | |
| 16.0 | 49.9 | 43.1 | 38.0 | | |
| 18.0 | 44.9 | 39.5 | 35.3 | | |
| 20.0 | 39.2 | 36.6 | 33.0 | 28.1 | |
| 22.0 | 34.1 | 34.0 | 31.0 | 26.8 | 19.4 |
| 24.0 | 30.0 | 30.7 | 29.3 | 25.7 | 18.9 |
| 26.0 | 26.6 | 27.2 | 27.8 | 24.7 | 18.6 |
| 28.0 | 23.8 | 24.3 | 24.8 | 23.9 | 18.4 |
| 30.0 | 21.4 | 21.9 | 22.3 | 22.8 | |
| 32.0 | 19.4 | 19.8 | 20.1 | 20.4 | |
| 34.0 | 17.7 | 17.9 | 18.1 | | |
| 36.0 | 16.2 | 16.3 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 6 | 6 | 6 | 6 | 6 |

HA 性能

22.7m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 11.0 | 45.0 | | | | |
| 12.0 | 45.0 | | | | |
| 14.0 | 45.0 | | | | |
| 16.0 | 45.0 | 45.0 | | | |
| 18.0 | 41.9 | 44.0 | 39.5 | | |
| 20.0 | 36.3 | 38.2 | 37.2 | | |
| 22.0 | 31.5 | 32.9 | 34.2 | 30.0 | |
| 24.0 | 27.4 | 28.6 | 29.7 | 28.9 | 22.1 |
| 26.0 | 24.0 | 25.1 | 26.0 | 27.3 | 21.7 |
| 28.0 | 21.2 | 22.1 | 23.0 | 24.1 | 21.3 |
| 30.0 | 18.9 | 19.7 | 20.4 | 21.3 | 21.1 |
| 32.0 | 16.8 | 17.5 | 18.2 | 18.9 | 19.4 |
| 34.0 | 15.1 | 15.7 | 16.2 | 16.9 | |
| 36.0 | 13.6 | 14.1 | 14.5 | 15.0 | |
| 38.0 | 12.2 | 12.6 | 13.0 | 13.3 | |
| 40.0 | 11.0 | 11.3 | 11.6 | | |
| 42.0 | 9.9 | 10.2 | 10.4 | | |
| 44.0 | 8.8 | 9.0 | | | |
| 46.0 | 7.7 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HA 性能

18.15m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 10.0 | 50.0 | | | | |
| 11.0 | 50.0 | | | | |
| 12.0 | 50.0 | | | | |
| 14.0 | 50.0 | 49.4 | | | |
| 16.0 | 50.0 | 45.2 | | | |
| 18.0 | 43.1 | 41.7 | 36.4 | | |
| 20.0 | 37.5 | 38.7 | 34.3 | | |
| 22.0 | 32.5 | 33.7 | 32.3 | 28.2 | |
| 24.0 | 28.4 | 29.4 | 30.3 | 27.1 | 20.6 |
| 26.0 | 25.1 | 25.9 | 26.7 | 26.2 | 20.2 |
| 28.0 | 22.3 | 23.0 | 23.7 | 24.6 | 19.9 |
| 30.0 | 19.9 | 20.6 | 21.1 | 21.9 | 19.7 |
| 32.0 | 17.9 | 18.4 | 18.9 | 19.5 | |
| 34.0 | 16.2 | 16.6 | 17.0 | 17.4 | |
| 36.0 | 14.6 | 15.0 | 15.3 | | |
| 38.0 | 13.3 | 13.6 | 13.8 | | |
| 40.0 | 12.1 | 12.3 | | | |
| 42.0 | 11.0 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 6 | 6 | 6 | 6 | 6 |

HA 性能

31.8m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 14.0 | 30.0 | | | | |
| 16.0 | 30.0 | 29.8 | | | |
| 18.0 | 30.0 | 28.9 | | | |
| 20.0 | 30.0 | 28.0 | 25.2 | | |
| 22.0 | 30.0 | 27.3 | 24.6 | | |
| 24.0 | 26.8 | 26.6 | 24.1 | 20.6 | |
| 26.0 | 23.4 | 24.6 | 23.7 | 20.3 | 17.0 |
| 28.0 | 20.6 | 21.7 | 22.6 | 20.1 | 16.9 |
| 30.0 | 18.3 | 19.2 | 20.1 | 19.9 | 16.9 |
| 32.0 | 16.3 | 17.1 | 17.9 | 18.8 | 16.9 |
| 34.0 | 14.5 | 15.2 | 15.9 | 16.8 | 16.9 |
| 36.0 | 13.0 | 13.6 | 14.2 | 14.9 | 15.3 |
| 38.0 | 11.6 | 12.2 | 12.7 | 13.3 | |
| 40.0 | 10.3 | 11.0 | 11.4 | 11.9 | |
| 42.0 | 9.1 | 9.7 | 10.2 | 10.6 | |
| 44.0 | 8.0 | 8.6 | 9.0 | 9.4 | |
| 46.0 | 7.0 | 7.5 | 7.8 | | |
| 48.0 | 6.1 | 6.5 | 6.8 | | |
| 50.0 | 5.3 | 5.6 | 5.8 | | |
| 55.0 | 3.5 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HA 性能

40.9m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 20.0 | | | | |
| 18.0 | 20.0 | | | | |
| 20.0 | 20.0 | 20.0 | | | |
| 22.0 | 20.0 | 20.0 | 20.0 | | |
| 24.0 | 20.0 | 20.0 | 20.0 | | |
| 26.0 | 20.0 | 20.0 | 20.0 | 20.0 | |
| 28.0 | 20.0 | 20.0 | 20.0 | 20.0 | 20.0 |
| 30.0 | 18.1 | 19.1 | 20.0 | 20.0 | 20.0 |
| 32.0 | 16.1 | 17.0 | 17.9 | 18.9 | 19.7 |
| 34.0 | 14.3 | 15.2 | 15.9 | 16.9 | 17.5 |
| 36.0 | 12.8 | 13.5 | 14.2 | 15.1 | 15.6 |
| 38.0 | 11.4 | 12.1 | 12.7 | 13.5 | 13.9 |
| 40.0 | 10.0 | 10.9 | 11.4 | 12.0 | 12.4 |
| 42.0 | 8.8 | 9.6 | 10.2 | 10.8 | |
| 44.0 | 7.7 | 8.4 | 9.0 | 9.6 | |
| 46.0 | 6.7 | 7.3 | 7.9 | 8.4 | |
| 48.0 | 5.8 | 6.4 | 6.8 | 7.3 | |
| 50.0 | 4.9 | 5.4 | 5.8 | 6.2 | |
| 55.0 | 3.1 | 3.4 | 3.7 | | |
| 危険角度 (°) | 28 | 28 | 30 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

50.0m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 11.0 | | | | |
| 20.0 | 11.0 | | | | |
| 22.0 | 11.0 | 11.0 | | | |
| 24.0 | 11.0 | 11.0 | 11.0 | | |
| 26.0 | 11.0 | 11.0 | 11.0 | | |
| 28.0 | 11.0 | 11.0 | 10.9 | 9.1 | |
| 30.0 | 11.0 | 11.0 | 10.8 | 9.1 | 7.5 |
| 32.0 | 11.0 | 11.0 | 10.6 | 9.0 | 7.5 |
| 34.0 | 11.0 | 11.0 | 10.5 | 9.0 | 7.5 |
| 36.0 | 11.0 | 11.0 | 10.4 | 8.9 | 7.5 |
| 38.0 | 10.9 | 11.0 | 10.4 | 8.9 | 7.5 |
| 40.0 | 9.6 | 10.5 | 10.3 | 8.9 | 7.5 |
| 42.0 | 8.4 | 9.2 | 10.0 | 8.9 | 7.5 |
| 44.0 | 7.3 | 8.1 | 8.8 | 8.9 | 7.5 |
| 46.0 | 6.3 | 7.0 | 7.6 | 8.4 | |
| 48.0 | 5.3 | 6.0 | 6.6 | 7.2 | |
| 50.0 | 4.5 | 5.1 | 5.6 | 6.2 | |
| 55.0 | | 3.1 | 3.5 | 3.9 | |
| 危険角度 (°) | 41 | 42 | 42 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

45.5m ブーム +4.4m+22.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 16.0 | | | | |
| 18.0 | 16.0 | | | | |
| 20.0 | 16.0 | 16.0 | | | |
| 22.0 | 16.0 | 16.0 | | | |
| 24.0 | 16.0 | 16.0 | 16.0 | | |
| 26.0 | 16.0 | 16.0 | 16.0 | | |
| 28.0 | 16.0 | 16.0 | 16.0 | 15.6 | |
| 30.0 | 16.0 | 16.0 | 16.0 | 15.4 | 13.0 |
| 32.0 | 15.9 | 16.0 | 16.0 | 15.3 | 13.0 |
| 34.0 | 14.1 | 15.0 | 15.8 | 15.2 | 12.9 |
| 36.0 | 12.6 | 13.4 | 14.1 | 15.0 | 12.9 |
| 38.0 | 11.1 | 12.0 | 12.6 | 13.4 | 12.9 |
| 40.0 | 9.8 | 10.7 | 11.3 | 12.0 | 12.4 |
| 42.0 | 8.6 | 9.4 | 10.1 | 10.7 | 11.0 |
| 44.0 | 7.5 | 8.2 | 8.9 | 9.6 | |
| 46.0 | 6.5 | 7.2 | 7.8 | 8.4 | |
| 48.0 | 5.6 | 6.2 | 6.7 | 7.3 | |
| 50.0 | 4.7 | 5.3 | 5.8 | 6.2 | |
| 55.0 | 2.9 | 3.3 | 3.6 | | |
| 危険角度 (°) | 36 | 36 | 36 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

13.6m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 14.0 | 35.0 | | | | |
| 16.0 | 34.4 | | | | |
| 18.0 | 34.4 | 33.8 | | | |
| 20.0 | 34.4 | 31.5 | | | |
| 22.0 | 32.8 | 29.1 | 26.1 | | |
| 24.0 | 30.2 | 27.1 | 24.5 | | |
| 26.0 | 27.7 | 25.3 | 23.1 | | |
| 28.0 | 24.9 | 23.7 | 21.8 | 18.8 | |
| 30.0 | 22.5 | 22.4 | 20.7 | 18.0 | |
| 32.0 | 20.4 | 21.0 | 19.7 | 17.3 | 12.7 |
| 34.0 | 18.6 | 19.1 | 18.9 | 16.7 | 12.4 |
| 36.0 | 17.0 | 17.5 | 18.0 | 16.2 | 12.2 |
| 38.0 | 15.7 | 16.1 | 16.5 | 15.8 | |
| 40.0 | 14.4 | 14.8 | 15.1 | 15.5 | |
| 42.0 | 13.4 | 13.6 | 13.9 | | |
| 44.0 | 12.4 | 12.6 | 12.7 | | |
| 46.0 | 11.5 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HA 性能

22.7m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 30.0 | | | | |
| 18.0 | 30.0 | | | | |
| 20.0 | 30.0 | 30.0 | | | |
| 22.0 | 30.0 | 30.0 | | | |
| 24.0 | 28.8 | 29.6 | 25.8 | | |
| 26.0 | 25.3 | 26.8 | 24.5 | | |
| 28.0 | 22.5 | 23.8 | 23.3 | | |
| 30.0 | 20.1 | 21.2 | 22.2 | 19.4 | |
| 32.0 | 18.0 | 19.0 | 20.0 | 18.7 | |
| 34.0 | 16.2 | 17.1 | 18.0 | 18.2 | 14.5 |
| 36.0 | 14.7 | 15.5 | 16.3 | 17.4 | 14.2 |
| 38.0 | 13.3 | 14.0 | 14.7 | 15.7 | 14.1 |
| 40.0 | 12.1 | 12.7 | 13.3 | 14.2 | 13.9 |
| 42.0 | 11.0 | 11.5 | 12.1 | 12.8 | |
| 44.0 | 10.0 | 10.5 | 11.0 | 11.5 | |
| 46.0 | 9.1 | 9.5 | 9.9 | 10.4 | |
| 48.0 | 8.1 | 8.6 | 9.0 | | |
| 50.0 | 7.3 | 7.7 | 8.0 | | |
| 55.0 | 5.4 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HA 性能

18.15m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 14.0 | 34.0 | | | | |
| 16.0 | 34.0 | | | | |
| 18.0 | 34.0 | 34.0 | | | |
| 20.0 | 34.0 | 32.8 | | | |
| 22.0 | 34.0 | 30.4 | 26.8 | | |
| 24.0 | 29.9 | 28.4 | 25.2 | | |
| 26.0 | 26.4 | 26.6 | 23.8 | | |
| 28.0 | 23.6 | 24.6 | 22.6 | 19.8 | |
| 30.0 | 21.2 | 22.1 | 21.5 | 19.1 | |
| 32.0 | 19.1 | 19.9 | 20.6 | 18.4 | 13.9 |
| 34.0 | 17.3 | 18.1 | 18.8 | 17.8 | 13.6 |
| 36.0 | 15.8 | 16.4 | 17.1 | 17.3 | 13.4 |
| 38.0 | 14.4 | 15.0 | 15.5 | 16.3 | 13.2 |
| 40.0 | 13.2 | 13.7 | 14.1 | 14.8 | |
| 42.0 | 12.1 | 12.5 | 12.9 | 13.4 | |
| 44.0 | 11.1 | 11.4 | 11.8 | 12.1 | |
| 46.0 | 10.2 | 10.5 | 10.7 | | |
| 48.0 | 9.4 | 9.6 | 9.7 | | |
| 50.0 | 8.6 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 83t | 83t | 83t | 83t | 83t |
| フック質量 (t) | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| 巻掛本数 | 4 | 4 | 4 | 4 | 4 |

HA 性能

31.8m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 20.0 | | | | |
| 18.0 | 20.0 | | | | |
| 20.0 | 20.0 | | | | |
| 22.0 | 20.0 | 20.0 | | | |
| 24.0 | 20.0 | 20.0 | | | |
| 26.0 | 20.0 | 20.0 | 19.4 | | |
| 28.0 | 20.0 | 20.0 | 18.9 | | |
| 30.0 | 19.7 | 20.0 | 18.5 | 15.6 | |
| 32.0 | 17.6 | 18.8 | 18.1 | 15.3 | |
| 34.0 | 15.8 | 16.9 | 17.7 | 15.1 | 12.4 |
| 36.0 | 14.2 | 15.2 | 16.1 | 14.9 | 12.3 |
| 38.0 | 12.9 | 13.7 | 14.6 | 14.7 | 12.3 |
| 40.0 | 11.6 | 12.4 | 13.2 | 14.2 | 12.2 |
| 42.0 | 10.5 | 11.3 | 11.9 | 12.8 | 12.2 |
| 44.0 | 9.5 | 10.2 | 10.8 | 11.6 | 12.0 |
| 46.0 | 8.4 | 9.2 | 9.8 | 10.4 | 10.8 |
| 48.0 | 7.5 | 8.2 | 8.8 | 9.4 | |
| 50.0 | 6.6 | 7.3 | 7.9 | 8.4 | |
| 55.0 | 4.7 | 5.2 | 5.6 | | |
| 60.0 | 3.2 | 3.4 | | | |
| 危険角度 (°) | 13 | 20 | 30 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

40.9m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 14.0 | | | | |
| 20.0 | 14.0 | | | | |
| 22.0 | 14.0 | | | | |
| 24.0 | 14.0 | 14.0 | | | |
| 26.0 | 14.0 | 14.0 | | | |
| 28.0 | 14.0 | 14.0 | 14.0 | | |
| 30.0 | 14.0 | 14.0 | 14.0 | | |
| 32.0 | 14.0 | 14.0 | 14.0 | | |
| 34.0 | 14.0 | 14.0 | 14.0 | 14.0 | |
| 36.0 | 13.7 | 14.0 | 14.0 | 14.0 | |
| 38.0 | 12.3 | 13.3 | 14.0 | 14.0 | 14.0 |
| 40.0 | 11.1 | 12.0 | 12.9 | 14.0 | 14.0 |
| 42.0 | 9.9 | 10.9 | 11.6 | 12.6 | 13.4 |
| 44.0 | 8.8 | 9.8 | 10.5 | 11.4 | 12.0 |
| 46.0 | 7.7 | 8.7 | 9.5 | 10.3 | 10.8 |
| 48.0 | 6.8 | 7.7 | 8.5 | 9.3 | 9.7 |
| 50.0 | 5.9 | 6.8 | 7.5 | 8.4 | 8.7 |
| 55.0 | 4.1 | 4.7 | 5.3 | 5.9 | |
| 60.0 | | 3.0 | 3.4 | 3.8 | |
| 危険角度 (°) | 36 | 37 | 37 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

50.0m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.0 | | | | |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | 9.0 | | | |
| 28.0 | 9.0 | 9.0 | | | |
| 30.0 | 9.0 | 9.0 | 7.8 | | |
| 32.0 | 9.0 | 8.8 | 7.7 | | |
| 34.0 | 9.0 | 8.6 | 7.5 | | |
| 36.0 | 9.0 | 8.4 | 7.4 | 6.0 | |
| 38.0 | 9.0 | 8.2 | 7.3 | 5.9 | 4.7 |
| 40.0 | 9.0 | 8.1 | 7.2 | 5.9 | 4.6 |
| 42.0 | 8.9 | 8.0 | 7.1 | 5.8 | 4.6 |
| 44.0 | 8.2 | 7.9 | 7.0 | 5.8 | 4.6 |
| 46.0 | 7.2 | 7.8 | 7.0 | 5.8 | 4.6 |
| 48.0 | 6.2 | 7.3 | 6.9 | 5.8 | 4.6 |
| 50.0 | 5.4 | 6.3 | 6.9 | 5.8 | 4.6 |
| 55.0 | 3.5 | 4.3 | 5.0 | 5.8 | |
| 60.0 | | | 3.1 | 3.7 | |
| 危険角度 (°) | 47 | 47 | 48 | 48 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

45.5m ブーム +4.4m+31.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | 11.1 | |
| 36.0 | 12.0 | 12.0 | 12.0 | 11.0 | |
| 38.0 | 12.0 | 12.0 | 12.0 | 10.9 | 8.9 |
| 40.0 | 10.8 | 11.8 | 12.0 | 10.8 | 8.9 |
| 42.0 | 9.6 | 10.7 | 11.5 | 10.7 | 8.8 |
| 44.0 | 8.5 | 9.6 | 10.4 | 10.6 | 8.8 |
| 46.0 | 7.4 | 8.5 | 9.4 | 10.2 | 8.8 |
| 48.0 | 6.5 | 7.5 | 8.4 | 9.2 | 8.8 |
| 50.0 | 5.6 | 6.5 | 7.4 | 8.3 | 8.7 |
| 55.0 | 3.8 | 4.5 | 5.2 | 5.9 | |
| 60.0 | | 2.8 | 3.3 | 3.8 | |
| 危険角度 (°) | 42 | 43 | 43 | 45 | 60 |
| フック種類 | 24t | 24t | 24t | 24t | 24t |
| フック質量 (t) | 0.88 | 0.88 | 0.88 | 0.88 | 0.88 |
| 巻掛本数 | 2 | 2 | 2 | 2 | 2 |

HA 性能

13.6m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 16.0 | 12.0 | | | | |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | 12.0 | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | 12.0 | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | 11.8 | |
| 38.0 | 12.0 | 12.0 | 12.0 | 11.2 | |
| 40.0 | 12.0 | 12.0 | 11.9 | 10.7 | 9.4 |
| 42.0 | 12.0 | 12.0 | 11.3 | 10.2 | 9.2 |
| 44.0 | 12.0 | 11.5 | 10.7 | 9.8 | 9.0 |
| 46.0 | 11.6 | 10.9 | 10.3 | 9.5 | 8.9 |
| 48.0 | 10.9 | 10.3 | 9.8 | 9.2 | |
| 50.0 | 10.3 | 9.9 | 9.5 | 9.0 | |
| 55.0 | 9.1 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

22.7m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | 12.0 | |
| 38.0 | 12.0 | 12.0 | 12.0 | 11.7 | |
| 40.0 | 12.0 | 12.0 | 12.0 | 11.3 | |
| 42.0 | 12.0 | 12.0 | 12.0 | 10.8 | 9.7 |
| 44.0 | 11.2 | 12.0 | 11.9 | 10.5 | 9.5 |
| 46.0 | 10.3 | 11.0 | 11.4 | 10.1 | 9.3 |
| 48.0 | 9.5 | 10.1 | 10.7 | 9.8 | 9.1 |
| 50.0 | 8.7 | 9.3 | 9.8 | 9.5 | 9.0 |
| 55.0 | 6.9 | 7.5 | 7.9 | 8.3 | |
| 60.0 | 5.3 | 5.7 | 6.0 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

18.15m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | 12.0 | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | 12.0 | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | 12.0 | |
| 38.0 | 12.0 | 12.0 | 12.0 | 11.5 | |
| 40.0 | 12.0 | 12.0 | 12.0 | 11.0 | 9.9 |
| 42.0 | 12.0 | 12.0 | 11.9 | 10.6 | 9.6 |
| 44.0 | 12.0 | 12.0 | 11.4 | 10.2 | 9.3 |
| 46.0 | 11.3 | 11.7 | 10.9 | 9.8 | 9.2 |
| 48.0 | 10.4 | 10.9 | 10.4 | 9.5 | 9.0 |
| 50.0 | 9.7 | 10.1 | 10.0 | 9.3 | |
| 55.0 | 8.0 | 8.3 | 8.5 | | |
| 60.0 | 6.6 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

31.8m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 12.0 | 12.0 | 12.0 | 12.0 | |
| 40.0 | 12.0 | 12.0 | 12.0 | 11.7 | |
| 42.0 | 11.6 | 12.0 | 12.0 | 11.3 | |
| 44.0 | 10.6 | 11.5 | 12.0 | 10.9 | 9.5 |
| 46.0 | 9.7 | 10.5 | 11.3 | 10.6 | 9.4 |
| 48.0 | 8.8 | 9.6 | 10.3 | 10.3 | 9.3 |
| 50.0 | 8.0 | 8.8 | 9.5 | 10.0 | 9.2 |
| 55.0 | 6.1 | 6.9 | 7.5 | 8.2 | 8.5 |
| 60.0 | 4.5 | 5.1 | 5.7 | 6.3 | |
| 65.0 | 3.1 | 3.5 | 3.9 | | |
| 70.0 | 1.9 | 2.1 | | | |
| 危険角度 (°) | 11 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

40.9m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 11.0 | | | | |
| 24.0 | 11.0 | | | | |
| 26.0 | 11.0 | | | | |
| 28.0 | 11.0 | 11.0 | | | |
| 30.0 | 11.0 | 11.0 | | | |
| 32.0 | 11.0 | 11.0 | | | |
| 34.0 | 11.0 | 11.0 | 11.0 | | |
| 36.0 | 11.0 | 11.0 | 11.0 | | |
| 38.0 | 11.0 | 11.0 | 11.0 | | |
| 40.0 | 11.0 | 11.0 | 11.0 | | |
| 42.0 | 11.0 | 11.0 | 11.0 | 11.0 | |
| 44.0 | 10.1 | 11.0 | 11.0 | 11.0 | |
| 46.0 | 9.1 | 10.1 | 11.0 | 11.0 | 9.6 |
| 48.0 | 8.1 | 9.2 | 10.0 | 10.7 | 9.5 |
| 50.0 | 7.3 | 8.4 | 9.1 | 10.2 | 9.3 |
| 55.0 | 5.3 | 6.3 | 7.2 | 8.0 | 8.6 |
| 60.0 | 3.7 | 4.5 | 5.3 | 6.1 | |
| 65.0 | 2.4 | 3.0 | 3.6 | 4.2 | |
| 70.0 | | 1.7 | 2.1 | | |
| 危険角度 (°) | 35 | 36 | 36 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

50.0m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 7.0 | | | | |
| 26.0 | 7.0 | | | | |
| 28.0 | 7.0 | | | | |
| 30.0 | 7.0 | 7.0 | | | |
| 32.0 | 7.0 | 7.0 | | | |
| 34.0 | 7.0 | 7.0 | | | |
| 36.0 | 7.0 | 6.8 | 5.9 | | |
| 38.0 | 7.0 | 6.7 | 5.8 | | |
| 40.0 | 7.0 | 6.5 | 5.6 | | |
| 42.0 | 7.0 | 6.4 | 5.5 | | |
| 44.0 | 7.0 | 6.2 | 5.4 | 4.3 | |
| 46.0 | 6.9 | 6.1 | 5.3 | 4.2 | |
| 48.0 | 6.7 | 6.0 | 5.2 | 4.2 | 3.1 |
| 50.0 | 6.6 | 5.9 | 5.2 | 4.1 | 3.1 |
| 55.0 | 4.7 | 5.7 | 5.0 | 4.1 | 3.1 |
| 60.0 | 3.1 | 4.1 | 4.9 | 4.1 | 3.1 |
| 65.0 | 1.8 | 2.5 | 3.3 | 4.1 | |
| 70.0 | | | 1.8 | 2.4 | |
| 危険角度 (°) | 47 | 48 | 48 | 48 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

45.5m ブーム +4.4m+40.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 10.0 | | | | |
| 26.0 | 10.0 | | | | |
| 28.0 | 10.0 | | | | |
| 30.0 | 10.0 | 10.0 | | | |
| 32.0 | 10.0 | 10.0 | | | |
| 34.0 | 10.0 | 10.0 | | | |
| 36.0 | 10.0 | 10.0 | 10.0 | | |
| 38.0 | 10.0 | 10.0 | 10.0 | | |
| 40.0 | 10.0 | 10.0 | 10.0 | | |
| 42.0 | 10.0 | 10.0 | 10.0 | 8.5 | |
| 44.0 | 9.8 | 10.0 | 10.0 | 8.3 | |
| 46.0 | 8.8 | 9.9 | 9.9 | 8.2 | 6.6 |
| 48.0 | 7.8 | 9.0 | 9.8 | 8.1 | 6.5 |
| 50.0 | 6.9 | 8.1 | 9.0 | 8.1 | 6.5 |
| 55.0 | 5.0 | 6.0 | 7.0 | 7.9 | 6.5 |
| 60.0 | 3.4 | 4.3 | 5.1 | 6.0 | 6.5 |
| 65.0 | 2.1 | 2.8 | 3.4 | 4.2 | |
| 70.0 | | 1.5 | 2.0 | 2.5 | |
| 危険角度 (°) | 41 | 42 | 42 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

13.6m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 12.0 | | | | |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | 12.0 | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 11.7 | | |
| 38.0 | 12.0 | 12.0 | 10.9 | | |
| 40.0 | 12.0 | 11.2 | 10.3 | | |
| 42.0 | 11.5 | 10.5 | 9.7 | 8.6 | |
| 44.0 | 10.8 | 9.9 | 9.2 | 8.2 | |
| 46.0 | 10.1 | 9.4 | 8.7 | 7.8 | 7.1 |
| 48.0 | 9.5 | 8.8 | 8.2 | 7.5 | 6.9 |
| 50.0 | 8.9 | 8.4 | 7.9 | 7.2 | 6.7 |
| 55.0 | 7.8 | 7.4 | 7.1 | 6.6 | |
| 60.0 | 6.9 | 6.7 | 6.5 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

22.7m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 12.0 | 12.0 | 11.7 | | |
| 40.0 | 12.0 | 12.0 | 11.1 | | |
| 42.0 | 12.0 | 11.9 | 10.5 | 8.9 | |
| 44.0 | 11.7 | 11.2 | 10.0 | 8.6 | |
| 46.0 | 10.8 | 10.6 | 9.5 | 8.2 | |
| 48.0 | 9.9 | 10.1 | 9.1 | 7.9 | 7.1 |
| 50.0 | 9.2 | 9.6 | 8.7 | 7.6 | 6.9 |
| 55.0 | 7.5 | 8.1 | 7.8 | 7.0 | 6.5 |
| 60.0 | 5.9 | 6.5 | 7.0 | 6.6 | |
| 65.0 | 4.5 | 5.0 | 5.3 | | |
| 70.0 | 3.3 | 3.5 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

18.15m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 12.0 | | | | |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | 12.0 | | | |
| 28.0 | 12.0 | 12.0 | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | | | |
| 34.0 | 12.0 | 12.0 | 12.0 | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 12.0 | 12.0 | 11.3 | | |
| 40.0 | 12.0 | 12.0 | 10.7 | | |
| 42.0 | 12.0 | 11.2 | 10.1 | 8.8 | |
| 44.0 | 11.7 | 10.6 | 9.6 | 8.4 | |
| 46.0 | 11.0 | 10.0 | 9.1 | 8.0 | |
| 48.0 | 10.4 | 9.5 | 8.7 | 7.7 | 7.0 |
| 50.0 | 9.8 | 9.0 | 8.3 | 7.4 | 6.8 |
| 55.0 | 8.4 | 8.0 | 7.4 | 6.8 | 6.5 |
| 60.0 | 7.0 | 7.1 | 6.8 | 6.5 | |
| 65.0 | 5.8 | 6.0 | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

31.8m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 12.0 | | | | |
| 24.0 | 12.0 | | | | |
| 26.0 | 12.0 | | | | |
| 28.0 | 12.0 | | | | |
| 30.0 | 12.0 | 12.0 | | | |
| 32.0 | 12.0 | 12.0 | | | |
| 34.0 | 12.0 | 12.0 | | | |
| 36.0 | 12.0 | 12.0 | 12.0 | | |
| 38.0 | 12.0 | 12.0 | 12.0 | | |
| 40.0 | 12.0 | 12.0 | 11.8 | | |
| 42.0 | 12.0 | 12.0 | 11.2 | | |
| 44.0 | 11.0 | 12.0 | 10.7 | 8.8 | |
| 46.0 | 10.1 | 11.1 | 10.2 | 8.5 | |
| 48.0 | 9.3 | 10.2 | 9.8 | 8.2 | |
| 50.0 | 8.5 | 9.4 | 9.4 | 8.0 | 7.0 |
| 55.0 | 6.6 | 7.6 | 8.2 | 7.4 | 6.7 |
| 60.0 | 5.0 | 5.8 | 6.6 | 6.9 | 6.5 |
| 65.0 | 3.6 | 4.3 | 4.9 | 5.7 | |
| 70.0 | 2.4 | 2.9 | 3.4 | 3.8 | |
| 75.0 | 1.4 | 1.7 | 2.0 | | |
| 危険角度 (°) | 21 | 21 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

40.9m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 8.0 | | | | |
| 28.0 | 8.0 | | | | |
| 30.0 | 8.0 | | | | |
| 32.0 | 8.0 | 8.0 | | | |
| 34.0 | 8.0 | 8.0 | | | |
| 36.0 | 8.0 | 8.0 | | | |
| 38.0 | 8.0 | 8.0 | | | |
| 40.0 | 8.0 | 8.0 | 8.0 | | |
| 42.0 | 8.0 | 8.0 | 8.0 | | |
| 44.0 | 8.0 | 8.0 | 8.0 | | |
| 46.0 | 8.0 | 8.0 | 8.0 | | |
| 48.0 | 8.0 | 8.0 | 8.0 | 8.0 | |
| 50.0 | 7.8 | 8.0 | 8.0 | 8.0 | |
| 55.0 | 5.8 | 7.0 | 7.9 | 7.7 | 6.8 |
| 60.0 | 4.2 | 5.2 | 6.1 | 7.2 | 6.6 |
| 65.0 | 2.8 | 3.7 | 4.5 | 5.5 | 6.0 |
| 70.0 | 1.7 | 2.4 | 3.0 | 3.7 | |
| 75.0 | | | 1.7 | 2.2 | |
| 危険角度 (°) | 40 | 41 | 41 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

50.0m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 5.0 | | | | |
| 28.0 | 5.0 | | | | |
| 30.0 | 5.0 | | | | |
| 32.0 | 5.0 | | | | |
| 34.0 | 5.0 | 5.0 | | | |
| 36.0 | 5.0 | 5.0 | | | |
| 38.0 | 5.0 | 5.0 | | | |
| 40.0 | 5.0 | 5.0 | 4.5 | | |
| 42.0 | 5.0 | 5.0 | 4.4 | | |
| 44.0 | 5.0 | 5.0 | 4.3 | | |
| 46.0 | 5.0 | 4.9 | 4.2 | | |
| 48.0 | 5.0 | 4.8 | 4.1 | 3.1 | |
| 50.0 | 5.0 | 4.7 | 4.0 | 3.0 | |
| 55.0 | 5.0 | 4.4 | 3.8 | 2.9 | 2.0 |
| 60.0 | 3.6 | 4.2 | 3.7 | 2.8 | 2.0 |
| 65.0 | 2.2 | 3.2 | 3.6 | 2.8 | 2.0 |
| 70.0 | | 1.9 | 2.6 | 2.8 | 2.0 |
| 75.0 | | | 1.3 | 2.1 | |
| 危険角度 (°) | 49 | 50 | 50 | 51 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

45.5m ブーム +4.4m+47.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 7.5 | | | | |
| 28.0 | 7.5 | | | | |
| 30.0 | 7.5 | | | | |
| 32.0 | 7.5 | | | | |
| 34.0 | 7.5 | 7.5 | | | |
| 36.0 | 7.5 | 7.5 | | | |
| 38.0 | 7.5 | 7.5 | | | |
| 40.0 | 7.5 | 7.5 | 7.5 | | |
| 42.0 | 7.5 | 7.5 | 7.5 | | |
| 44.0 | 7.5 | 7.5 | 7.5 | | |
| 46.0 | 7.5 | 7.5 | 7.5 | | |
| 48.0 | 7.5 | 7.5 | 7.5 | 6.7 | |
| 50.0 | 7.4 | 7.5 | 7.5 | 6.6 | |
| 55.0 | 5.5 | 6.7 | 7.5 | 6.4 | 4.9 |
| 60.0 | 3.9 | 4.9 | 5.9 | 6.2 | 4.9 |
| 65.0 | 2.5 | 3.4 | 4.3 | 5.3 | 4.9 |
| 70.0 | 1.3 | 2.1 | 2.8 | 3.7 | |
| 75.0 | | | 1.5 | 2.1 | |
| 危険角度 (°) | 45 | 46 | 47 | 47 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

13.6m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.3 | | | | |
| 26.0 | 9.3 | | | | |
| 28.0 | 9.3 | | | | |
| 30.0 | 9.1 | 8.9 | | | |
| 32.0 | 9.1 | 8.8 | | | |
| 34.0 | 9.0 | 8.8 | | | |
| 36.0 | 8.9 | 8.6 | | | |
| 38.0 | 8.7 | 8.2 | 7.7 | | |
| 40.0 | 8.4 | 7.9 | 7.4 | | |
| 42.0 | 8.0 | 7.6 | 7.2 | | |
| 44.0 | 7.7 | 7.3 | 6.9 | | |
| 46.0 | 7.4 | 7.0 | 6.7 | 6.2 | |
| 48.0 | 7.1 | 6.8 | 6.5 | 6.1 | |
| 50.0 | 6.9 | 6.6 | 6.3 | 5.9 | |
| 55.0 | 6.3 | 6.1 | 5.9 | 5.4 | 4.9 |
| 60.0 | 5.8 | 5.6 | 5.3 | 4.9 | 4.6 |
| 65.0 | 5.2 | 5.0 | 4.8 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

22.7m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 9.3 | | | | |
| 26.0 | 9.3 | | | | |
| 28.0 | 9.3 | | | | |
| 30.0 | 9.1 | | | | |
| 32.0 | 9.1 | 8.9 | | | |
| 34.0 | 9.1 | 8.8 | | | |
| 36.0 | 9.0 | 8.7 | | | |
| 38.0 | 8.9 | 8.6 | 7.9 | | |
| 40.0 | 8.8 | 8.3 | 7.7 | | |
| 42.0 | 8.7 | 8.0 | 7.4 | | |
| 44.0 | 8.4 | 7.7 | 7.2 | | |
| 46.0 | 8.1 | 7.5 | 7.0 | | |
| 48.0 | 7.8 | 7.2 | 6.8 | 6.2 | |
| 50.0 | 7.5 | 7.0 | 6.6 | 6.0 | |
| 55.0 | 6.9 | 6.5 | 6.2 | 5.7 | 5.1 |
| 60.0 | 6.3 | 6.1 | 5.8 | 5.2 | 4.8 |
| 65.0 | 4.9 | 5.6 | 5.3 | 4.8 | 4.6 |
| 70.0 | 3.7 | 4.2 | 4.7 | 4.6 | |
| 75.0 | 2.7 | 3.0 | 3.2 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

18.15m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.3 | | | | |
| 26.0 | 9.3 | | | | |
| 28.0 | 9.3 | | | | |
| 30.0 | 9.1 | 9.0 | | | |
| 32.0 | 9.1 | 9.0 | | | |
| 34.0 | 9.1 | 8.9 | | | |
| 36.0 | 8.9 | 8.8 | | | |
| 38.0 | 8.8 | 8.4 | 7.8 | | |
| 40.0 | 8.7 | 8.1 | 7.6 | | |
| 42.0 | 8.4 | 7.8 | 7.3 | | |
| 44.0 | 8.0 | 7.5 | 7.1 | | |
| 46.0 | 7.7 | 7.3 | 6.8 | | |
| 48.0 | 7.5 | 7.0 | 6.6 | 6.1 | |
| 50.0 | 7.2 | 6.8 | 6.4 | 6.0 | |
| 55.0 | 6.6 | 6.3 | 6.0 | 5.5 | 5.0 |
| 60.0 | 6.1 | 5.9 | 5.6 | 5.0 | 4.7 |
| 65.0 | 5.6 | 5.3 | 5.0 | 4.7 | |
| 70.0 | 4.9 | 4.8 | 4.7 | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

31.8m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | | | | |
| 32.0 | 9.0 | 8.9 | | | |
| 34.0 | 9.0 | 8.8 | | | |
| 36.0 | 9.0 | 8.7 | | | |
| 38.0 | 8.9 | 8.7 | | | |
| 40.0 | 8.8 | 8.7 | 7.9 | | |
| 42.0 | 8.7 | 8.4 | 7.6 | | |
| 44.0 | 8.7 | 8.1 | 7.4 | | |
| 46.0 | 8.7 | 7.9 | 7.2 | | |
| 48.0 | 8.4 | 7.6 | 7.0 | | |
| 50.0 | 8.1 | 7.4 | 6.8 | 6.1 | |
| 55.0 | 7.0 | 6.9 | 6.4 | 5.8 | |
| 60.0 | 5.4 | 6.4 | 6.1 | 5.5 | 4.9 |
| 65.0 | 4.0 | 4.8 | 5.7 | 5.1 | 4.7 |
| 70.0 | 2.8 | 3.5 | 4.2 | 4.8 | |
| 75.0 | 1.8 | 2.3 | 2.9 | 3.4 | |
| 80.0 | | | 1.6 | | |
| 危険角度 (°) | 31 | 31 | 31 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

40.9m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | | | | |
| 34.0 | 6.0 | | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | | | |
| 40.0 | 6.0 | 6.0 | | | |
| 42.0 | 6.0 | 6.0 | | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | | |
| 50.0 | 6.0 | 6.0 | 6.0 | | |
| 55.0 | 6.0 | 6.0 | 6.0 | 5.9 | |
| 60.0 | 4.6 | 5.8 | 6.0 | 5.7 | 4.9 |
| 65.0 | 3.2 | 4.2 | 5.2 | 5.3 | 4.7 |
| 70.0 | 2.0 | 2.9 | 3.7 | 4.8 | 4.6 |
| 75.0 | | 1.7 | 2.4 | 3.3 | |
| 80.0 | | | | 1.8 | |
| 危険角度 (°) | 44 | 45 | 46 | 46 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

50.0m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | | | | |
| 34.0 | 4.1 | | | | |
| 36.0 | 4.1 | | | | |
| 38.0 | 4.1 | 4.1 | | | |
| 40.0 | 4.1 | 4.1 | | | |
| 42.0 | 4.1 | 4.1 | | | |
| 44.0 | 4.1 | 4.0 | | | |
| 46.0 | 4.1 | 3.9 | 3.2 | | |
| 48.0 | 4.1 | 3.8 | 3.1 | | |
| 50.0 | 4.1 | 3.7 | 3.0 | | |
| 55.0 | 4.0 | 3.4 | 2.8 | 2.0 | |
| 60.0 | 3.7 | 3.2 | 2.7 | 1.9 | |
| 65.0 | 2.5 | 3.1 | 2.6 | 1.8 | |
| 70.0 | | 2.4 | 2.5 | 1.8 | |
| 75.0 | | | 2.0 | 1.8 | |
| 80.0 | | | | 1.7 | |
| 危険角度 (°) | 52 | 53 | 54 | 54 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |

HA 性能

45.5m ブーム +4.4m+54.0m ヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | | | | |
| 34.0 | 5.5 | | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | | | |
| 42.0 | 5.5 | 5.5 | | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | | |
| 55.0 | 5.5 | 5.5 | 5.5 | 5.2 | |
| 60.0 | 4.3 | 5.5 | 5.5 | 5.0 | 3.7 |
| 65.0 | 2.9 | 3.9 | 5.0 | 4.8 | 3.6 |
| 70.0 | 1.7 | 2.6 | 3.5 | 4.7 | 3.6 |
| 75.0 | | 1.4 | 2.2 | 3.2 | 3.6 |
| 80.0 | | | | 1.8 | |
| 危険角度 (°) | 48 | 49 | 50 | 51 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 巻掛本数 | 1 | 1 | 1 | 1 | 1 |